

J Hewit & Sons Ltd LEATHER MANUFACTURERS



12 Nettlehill Road Livingston WEST LOTHIAN EH54 5DL Tel: +44 (0) 1506 444160 Fax: +44 (0) 1506 437749 sales@hewit.com www.hewit.com

INSTRUCTIONS FOR THE ASSEMBLY OF WOODEN FINISHING PRESS

- 1. Place both jaws on a flat surface.
- 2. The front jaw should (the one without the thread holes) should be facing you.
- 3. Insert the handles into the front jaw and when in position knock the two retaining dowels in to place with a hammer. When the handles are locked in position, the should still be able to turn easily.
- 4. Attach the back jaw by placing (in the correct orientation) the threaded holes over the wooden screws and then by turning both handles clockwise simultaneously.

A GUIDE TO THE CARE AND MAINTENANCE OF ALL WOODEN PRESSES

Please accept the following as a guide to increasing the working life of our wooden laying and finishing presses.

- 1. Under no circumstances should any lubrication, polishes or waxes be put on the screw of the press. If any sticking occurs, then a small amount of silicone spray may be applied to the screws.
- 2. Keep out of direct sunlight and away from heat sources, i.e.: radiators, fan heaters, etc.
- 3. If the press is not in regular use, then it is advised that the equipment be regularly "opened and shut". This will help prevent the screws from sticking.

If you have any further enquired please do not hesitate to contact us.