

## J Hewit & Sons Ltd LEATHER MANUFACTURERS



12 Nettlehill Road Livingston WEST LOTHIAN EH54 5DL Tel: +44 (0) 1506 444160 Fax: +44 (0) 1506 437749 sales@hewit.com www.hewit.com

## INSTRUCTIONS FOR THE ASSEMBLY OF WOODEN LAYING PRESS

- 1. Place both jaws on a flat surface.
- 2. The front jaw should have the peg holes facing up
- 3. The back jaw should have the runner facing up with the internal threads to the back (outside)
- 4. Insert threaded screws, close completely and when fully closed tap in wooden pegs.

## A GUIDE TO THE CARE AND MAINTENANCE OF ALL WOODEN PRESSES

Please accept the following as a guide to increasing the working life of our wooden laying and finishing presses.

- Under no circumstances should any lubrication, polishes or waxes be put on the screw of the press. If any sticking occurs, then a small amount of silicone spray may be applied to the screws.
- 2. Keep out of direct sunlight and away from heat sources, i.e.: radiators, fan heaters, etc.
- 3. If the press is not in regular use, then it is advised that the equipment be regularly "opened and shut". This will help prevent the screws from sticking.

If you have any further enquired please do not hesitate to contact us.

Presses.doc 23/07/2010